



Seal Bond[®]
CONSTRUCTION SERIES

CS - 4200
All Weather

CS-4200 All Weather Construction Sealant

Description: Seal Bond CS-4200 is a high performance interior and exterior multipurpose sealant. CS-4200 provides superior adhesion, flexibility and durability in most climates and conditions including damp surface application and low temperatures. CS-4200 provides excellent UV resistance while maintaining a watertight bond.

Where to use: Seal Bond CS-4200 adheres to concrete, masonry, galvanized steel, wood PVC, vinyl, brick, SBS Mod Bit, fiber cement, stone, aluminum and other common construction materials. Common applications include: window and door frames, siding, gutters and general weather sealing.

Advantages:	Benefits:
Excellent weatherability	<i>Non-yellowing, long lasting performance</i>
Excellent adhesion	<i>Seals common construction substrates</i>
Extremely low VOC/ LEED compliant	<i>Environmentally friendly</i>
Permanently elastic	<i>Allows for movement over a broad temperature range</i>
Solvent and isocyanate free, 100% solids	<i>Safe to use, no shrinkage</i>
Paintable	<i>Consistent overall appearance</i>
Gunability at low temperatures	<i>Consistent ease of use</i>
Mildew resistant	<i>Remains clean and durable</i>

Packaging: 10.3 fluid oz (305ml) cartridges/28 fluid oz (828ml) cartridges.

Color: White (custom colors available)

Physical Properties:

Composition: Proprietary Hybrid Polymer

Consistency: Paste

Odor: Nil

Flammability: Nil

Specific Gravity: 1.5

Weathering Resistance: Excellent





Seal Bond[®]
CONSTRUCTION SERIES

CS-4200
All Weather

Test Data:

Elongation at break	280%	ASTM D-412
Tensile Strength	180 psi	ASTM D-412
Shore A Hardness	40	ASTM C-661
Shear Strength	120 lbf	ASTM D-1002
Tack Free Time	20 min	ASTM C-679
Slump	Non Sag	ASTM C-639
Shrinkage	No measurable shrinkage after 14 days	
Low Temperature Flex	Pass, -20°F	ASTM C-711
Service Temperature	-40°F to 200° F	Temporarily resistant to 390° F
Volatiles Content	16.99 g/L	ASTM D-2369

Storage and Self Life: Unopened containers should be stored in a cool and dry environment between 60°F and 80°F protected from water, heat and direct sunlight. Shelf life when stored properly is 10 months from date of manufacture.

Application Instructions: Surfaces should be clean and free of dust, dirt, loose paint, grease and oil. Frost or pooled water on surfaces should be removed before application. Seal Bond CS-4200 should be conditioned to room temperature before use. USDA Compliant for non-contact use in areas involving meat and poultry. This product can be applied at temperatures as low as 30° F.

Warranty: Manufacturer warrants that our products are manufactured and conform to strict quality assurance specifications for up to ten months of the date of manufacture. Improper use or storage may void warranty. Buyer and user understand that it is the sole responsibility to test and determine the suitability of the product for their practical purpose. Buyer's sole remedy for breach of warranty shall be strictly and exclusively limited to a refund of up to 100% of the purchase price of the non-conforming goods. This is the sole and exclusive remedy and liability for the defects or failure of this product. This warranty is in lieu of all other warranties, written or oral, statutory, expressed or implied, including warranties of merchantability or fitness for a particular purpose. Manufacturer shall not otherwise be liable for losses or damage related to application methods and uses, whether direct, indirect special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty or strict liability. For more information, please refer to the Seal Bond website www.seal-bond.com.

