

## **SEAL BOND HEAVY DUTY CLEANER**

### **Seal Bond HDC: Description**

SB HDC is a heavy duty cleaner formulated for versatility and dependability. Its uses can encompass anything from floor cleaning to hot dip tank cleaning. Worker safety is an integral part of the manufacturing process and this product contains no caustics, butyl ethers, or chlorinated and petroleum based solvents. Unlike many industrial strength cleaners, SB HDC is 100% biodegradable and environmentally safe. The versatility of this product is enhanced by complete water reducibility to assure the capability to customize the cleaning strength to meet your specific needs. SB HDC is a concentrated non-flammable detergent that dissolves a wide range of greases and oil based soils while leaving the area with a refreshing scent. Terpene hydrocarbons, the major component of oranges, and naturally occurring, are used in this product. As a water reducible cleaner, the ability to work with and around most metals is assured by the addition of flash rust additives and inhibitors. This product is compatible with most industrial coatings including epoxies and urethanes.

### **Recommended For:**

- Trucking Fleets
- Steel Mills
- Firms
- Manufacturers
- Foundries
- Military Installations

- Metal Fabricators
- Printing Plants
- Contract Cleaning
- U.S. Post Offices
- Waste Clean Up Firms

### **Directions for use:**

For heavy duty cleaning and degreasing, we recommend 1 part SB HDC to 4 parts water by volume. Deviations from this ratio can employ differing concentrations suited to the cleaning strength needed. For less soiled floors, dilute with more water and for heavily soiled floors, dilute with less water. Ratios varying from 1:1 to 50:1 (water:SB HDC) can be used for cleaning.

### **Application procedure:**

For cleaning dilute SB HDC to the desired strength and apply to the surface with a mopping action. Allow the solution to remain on the surface for approximately five minutes. Remove the loosened grime and dirt by mopping and then rinse the surface with clean water. For walls, woodwork, and enameled surfaces, apply the diluted SB HDC directly with a sponge or cloth. Wipe the surface clean with a clean, water dampened cloth or sponge. Always check product compatibility before using.

### **Limitations on Our Warranty**

We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Listed physical properties are typical and should not be construed as specifications. No warranty is made, expressed or implied, regarding such other information, the data on which it is based, or the results you will obtain from its use. No warranty is made, expressed or implied that our product shall be fit for any particular purpose. No warranty is made that the use of such information or our product will not infringe upon any patent. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Before using, read the material safety data sheet and follow all precautions.