

CS-4400 Block / Paver Adhesive

Description: Seal Bond CS-4400 is a high performance Landscape Adhesive designed for use with Bricks, Blocks, Pavers, Cement and Treated Wood. CS-4400 is a moisture curing adhesive that does not contain isocyanate or solvents. CS-4400 is environmentally friendly and can be used safely and effectively for bonding many masonry construction materials, as well as masonry to other common building substrates.

Where to use: Seal Bond CS-4400 is used to bond bricks, blocks, pavers, decorative stone, landscaping, walls, cement sidings and treated wood.

Advantages:	Benefits:
Solvent and isocyanate free	<i>Safe to use, low shrinkage</i>
Permanently elastic	<i>Allows for movement</i>
Extremely low VOC/LEED compliant	<i>Environmentally friendly</i>
Non-flammable	<i>Safe to use</i>
Low odor	<i>User friendly</i>
Replaceable cartridge nozzle	<i>No waste</i>
Remains flexible	<i>Absorbs vibration</i>
Freeze thaw stable	<i>Durable in wide temperature range</i>
Excellent gunability	<i>Easy to use</i>

Packaging: 10.3 fluid oz (305ml) cartridges/28 fluid oz (828ml) cartridges.

Color: White

Physical Properties:

Composition: Proprietary Hybrid Polymer

Consistency: Paste

Odor: Nil

Flammability: Nil

Test Data:

	50	ASTM C-661
Shear Strength	186 psi	ASTM D-1002
Tack Free Time	15 min	ASTM C-679
Cure Rate	7-10 days full cure	Application & environment dependent
Slump	N/A	
Shrinkage	Nil	
Low Temperature Flex	-20°F	Pass
Service Temperature	-40°F to 200°F	Temporarily resistant to 390°F
Adhesion In Peel – anodized aluminum	20.43pli	ASTM C-794

Storage and Self Life: Unopened containers should be stored in a cool and dry environment between 60°F and 80°F protected from water, heat and direct sunlight. Shelf life when stored properly is 10 months from date of manufacture.

Application Instructions: Surfaces should be clean and free of dust, dirt, loose paint, and grease. CS-4400 Brick Mastic should be applied in 1/8” beads running the full length of the substrate.

LIMITED WARRANTY

Seal Bond warrants that our products are manufactured and conform to strict quality assurance specifications. Improper use or storage may void warranty. Buyer understands that it is their sole responsibility to test and determine the suitability of the product for their practical purposes. Buyer's sole remedy for breach of warranty shall be strictly and exclusively limited to a refund of up to 100% of the purchase price of the non-conforming goods. This is the sole and exclusive remedy and liability for defects or failure of this product. This warranty is in lieu of all other warranties, written or oral, statutory, expressed or implied, including warranties of merchantability or fitness for a particular purpose. Manufacturer shall not otherwise be liable for losses or damages related to application methods and uses, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty or strict liability. For complete warranty information visit www.seal-bond.com