

Seal Bond® 132 White - Sprayable Adhesive/Sealant/Coating

SB 132: Description

Seal Bond® 132 is a multi-purpose product that is used as a sealant/seam sealer, an adhesive and a coating. This high-performance product is designed to provide excellent sprayability, yet it is also dispensed and tooled in a number of applications.

SEAM SEALING

Using a recommended Sprayable Seam Sealer Application Gun, SB 132 can provide a sprayed seam that matches the desired texture of many OEM applications. SB 132 is a high-performance seam sealer that can be caulked or sprayed. Applications include vehicle weld seams, floor and trunk pans as well as many other vehicle and non-vehicle applications. SB 132 can be spray painted immediately or painted with a brush after the sealer is tack free to the touch. Painting should be completed within 7 days of the initial application of SB 132.

BONDING

SB 132 is tough, elastic and waterproof. It bonds aggressively to steel, aluminum, ceramics, wood, Styrofoam®, glass, fiberglass and many plastics (including PVC and ABS).

COATING

SB 132 can also function as a stand-alone coating on many surfaces. Depending on the application, a coating of SB 132 may offer a protective coating, function as a sound deadener and/or provide anti-skid properties. A coating of SB 132 can also receive a number of paints. Paint compatibility should be tested, but can range from automotive finishes to many common Latex and some Alkyd paint systems.

Features and Benefits

- Odor Free
- Permanently elastic in a broad temperature range
- Paint compatible
- Silicone and Isocyanate free
- Non-shrinking, non -cracking
- Fast curing

Physical Properties

- Basic Material: Proprietary Polymer
- Consistency: Thin Paste
- Color: White
- Shelf Life: 10 months in unopened containers stored between 60° F and 80° F

Approximate Performance Properties

Elongation at Break	541%	ASTM D412-06
Hardness Shore A	38	ASTM D676
Initial Skin Forming	45 minutes	ASTM C679-03
Shear Strength	88.1 psi	ASTM D1002
Tensile Strength	256 psi	ASTM D412-06

Package Options:

10.3 ounce cartridges

5 Gallon Pails

50 Gallon Drums

LIMITED WARRANTY

Seal Bond warrants that our products are manufactured and conform to strict quality assurance specifications. Improper use or storage may void warranty. Buyer understands that it is their sole responsibility to test and determine the suitability of the product for their practical purposes. Buyer's sole remedy for breach of warranty shall be strictly and exclusively limited to a refund of up to 100% of the purchase price of the non-conforming goods. This is the sole and exclusive remedy and liability for defects or failure of this product. This warranty is in lieu of all other warranties, written or oral, statutory, expressed or implied, including warranties of merchantability or fitness for a particular purpose. Manufacturer shall not otherwise be liable for losses or damages related to application methods and uses, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty or strict liability. For complete warranty information visit www.seal-bond.com