



Seal Bond | 14851 Michael Lane | Spring Lake, MI 49456

(o) 800.252.4144 (f) 616.850.0530

[www.Seal-Bond.com](http://www.Seal-Bond.com)

## SEAL BOND® 140 Self Leveling Sealant/Coating

**SB 140** is a professional grade one-part, self-leveling, sealant/coating formulated for low movement joint and coating applications requiring quick cure and excellent weatherability including high UV resistance. **SB 140** reacts with moisture to form a strong yet flexible all-weather seal.

**SB 140** is tough, elastic and waterproof. It bonds aggressively to steel, aluminum, ceramics, coated metal, Styrofoam®, EPS, glass, wood and many plastics. **SB 140** is suited for many applications requiring adhesion to concrete and cementitious building materials. **SB 140** can be used in damp concrete joints; however pooled water and surface frost should be removed before application. Installation in high humidity conditions is acceptable.

### Benefits

- Solvent and isocyanate free, 100% solids
- Primer less bonding to most surfaces
- Odor Free
- Permanently elastic to -40°C
- Fast curing
- Paint compatible
- Non-flammable
- Provides water tight seal

### Physical Properties

- Basic Material: Proprietary Hybrid Polymer
- Consistency: Self-leveling fluid
- Color: Black, White and Limestone
- Odor: Nil
- Components: 1
- Type: Elastic
- Specific Gravity: 1.7
- Solvent Percentage: 0
- Isocyanate Percentage: 0
- Shelf Life: 11 months in unopened containers stored between 40° and 80° F.

### Approximate Performance Properties

Tensile Strength:	187 psi (7 day ambient cure)	ASTM D-412-06
Elongation at Break:	184% (7 day ambient cure)	ASTM D-412-06
Hardness Shore A:	48 (14 day ambient cure)	ASTM C-676
Initial Skin Formation:	15 minutes	ASTM C679-03
Accelerated Weathering:	No Cracking	No change to physicals
Stain Testing:	No Staining	
Low Temperature Flex:	-20°F	---PASS---
QUV Panel Test:	4000 hours B-bulb	
Service Temperature:	-40° to 200°F, temporarily resistant to 390°	

### Packaging Options

10.3 oz. Cartridges	1, 2 and 5 gallon pails
28 oz. Cartridges	50 gallon drums

### LIMITED WARRANTY

Seal Bond warrants that our products are manufactured and conform to strict quality assurance specifications. Improper use or storage may void warranty. Buyer understands that it is their sole responsibility to test and determine the suitability of the product for their practical purposes. Buyer's sole remedy for breach of warranty shall be strictly and exclusively limited to a refund of up to 100% of the purchase price of the non-conforming goods. This is the sole and exclusive remedy and liability for defects or failure of this product. This warranty is in lieu of all other warranties, written or oral, statutory, expressed or implied, including warranties of merchantability or fitness for a particular purpose. Manufacturer shall not otherwise be liable for losses or damages related to application methods and uses, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty or strict liability. For complete warranty information visit [www.seal-bond.com](http://www.seal-bond.com)