

TECHNICAL DATA SHEET

Seal Bond | 1251 E. Mt. Garfield Rd. | Norton Shores, MI 49444 (o) 800.2552.4144 (f) 616.850.0530 www.Seal-Bond.com

Seal Bond® Envirotec 105 Pedestal Adhesive

Description

Seal Bond® **Envirotec 105** Pedestal Adhesive is specifically designed for the installation of metal pedestals to concrete floors. Coverage will vary with pedestal size.

Application

Surfaces to which pedestals are to be bonded must be clean, dry, free of dust, dirt, paint, oils, wax and any other foreign matter. Apply adhesive to pedestal by the method normally used by a professional installer of access flooring. Full coverage of the pedestal is recommended with adhesive exuding from the pedestal base perimeter. Keep container sealed when not in use. Clean up with warm water while adhesive is still wet.

Benefits

- VOC Compliant
- Freeze Thaw Stable
- Bonds Metal to Concrete
- Easy Application and Clean Up
- Solvent & Isocyanate free
- Permanently elastic in a broad temperature range
- Low odor
- Non-flammable

Properties

- Recommended cure time: 45 days
- VOC's 6 g/L
- Base: Synthetic Polymer Blend
- Shelf Life: One year in unopened container @ 72°F

Cure Rate: Newly installed floor can be occupied in12-24 hours depending on the size and design of the access floor pedestal being installed and installation conditions.

For Overturning Moment testing, we recommend 21 day cure for best results.

Limitations

For interior use only. This adhesive is not recommended for use over concrete slabs where hydrostatic pressure, excessive moisture or high alkalinity (pH greater than 9) exists. Keep container sealed when not in use. Do not use when the temperature is below 50°F (10°C) or above 90°F (32°C). Sealed or coated concrete may affect adhesive performance. Field tests representing actual installation conditions and intended pedestal design are strongly recommended to confirm specific performance results.

Warranty

Seal Bond warrants that our products are manufactured and conform to strict quality assurance specifications.

For warranty information visit: www.seal-bond.com/terms