

Seal Bond[®] Envirotec 105 Pedestal Adhesive

Description

Seal Bond[®] Envirotec 105 Pedestal Adhesive is specifically designed for the installation of metal pedestals to concrete floors. Coverage will vary with pedestal size.

Application

Surfaces to which pedestals are to be bonded must be clean, dry, free of dust, dirt, paint, oils, wax and any other foreign matter. Apply adhesive to pedestal by the method normally used by a professional installer of access flooring. Full coverage of the pedestal is recommended with adhesive exuding from the pedestal base perimeter. Keep container sealed when not in use. Clean up with warm water while adhesive is still wet.

Benefits

- High Performance Adhesive
- VOC Compliant
- Freeze Thaw Stable
- Bonds Metal to Concrete
- Easy Application and Clean Up
- Solvent -free

Properties

V.O.C.: 6 g/L
Base: Synthetic Polymer Blend
Shelf Life: One year in unopened container @ 72°F.

Limitations

For interior use only. This adhesive is not recommended for use over concrete slabs where hydrostatic pressure, excessive moisture or high alkalinity (pH greater than 9) exists. Keep container sealed when not in use. Do not use when the temperature is below 50°F (10°C) or above 90°F (32°C). Sealed or coated concrete may affect adhesive performance. *Field tests representing actual installation conditions and intended pedestal design are strongly recommended to confirm specific performance results.*

LIMITED WARRANTY

Seal Bond warrants that our products are manufactured and conform to strict quality assurance specifications. Improper use or storage may void warranty. Buyer understands that it is their sole responsibility to test and determine the suitability of the product for their practical purposes. Buyer's sole remedy for breach of warranty shall be strictly and exclusively limited to a refund of up to 100% of the purchase price of the non-conforming goods. This is the sole and exclusive remedy and liability for defects or failure of this product. This warranty is in lieu of all other warranties, written or oral, statutory, expressed or implied, including warranties of merchantability or fitness for a particular purpose. Manufacturer shall not otherwise be liable for losses or damages related to application methods and uses, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty or strict liability. For complete warranty information visit www.seal-bond.com